

PERSTABIL®

PDS-2960-0001

Some applications of this product may be regulated or restricted by national or international standards (e.g. for food additives, water treatment, the pharmaceutical industry, etc). The buyer and the eventual user, in his sole and entire liability, shall respect those standards, orders of any relevant authority, and all existing patents and intellectual properties rights; and shall comply with the laws and the regulations applicable to our products and/or to his activity. The buyer and the eventual user must independently determine the suitability of this product for any particular purpose and its manner of use.

Product Identification:

Perstabil® is a non-flammable product. Perstabil® is mainly used in dry-cleaning because of its high solvent power towards fat and other soils and its mild nature towards delicate garments and ornaments.

Perstabil® is submitted to the directive 1999/13/EC on the limitation of emissions of volatile organic compounds (VOC). A guidance on the Solvents Emissions Directive for chlorinated solvent users is available at ECSA website: <http://www.eurochlor.org/solventsemissionsdirective#>.

Tetrachloroethene, Perchloroethylene	CCl ₂ = CCl ₂	ID Number	602-028-00-4
Molecular Mass	165,8	EC Number (EINECS)	204-825-9
CAS Number	127-18-4	UN Number	1897

For further information on product handling, transport, storage and product properties please consult our website:

<http://www.solvaychlorinatedorganics.com/library/bysection/result/0,0,- EN-1000019,00.html>

Product Specifications:

Characteristic	Unit	Value	Method of analysis
Purity (without Stabilizers)	g/kg	≥ 999	Gas chromatography (MOP 602958)
Colour	APHA	≤ 15	Colorimetry (MOP 603330)
Appearance		Clear without suspended matter	Visual test (ASTM D 3741/B)
Density range (D _{20/4})		≥ 1,620 ≤ 1,625	Oscillating U-tube (MOP 603326)
Non volatile Residue	mg/kg	≤ 30	Gravimetry (ASTM D 1353 / MOP 603423)
Alkalinity	mg/kg	≤ 30	Titrimetry (ASTM D 2989)
pH		≥ 8	pHmetry (MOP 603331)
Moisture (H ₂ O)	mg/kg	≤ 30	Coulometry - Karl Fischer method (ASTM E 1064)
Oxidising Compounds (Cl ₂)	mg/kg	≤ 1	Iodometry (ASTM D 4755)

Production Plant:

Tavaux (France).

Packaging Characteristics and Shelf Life:

Perstabil® can be supplied in bulk or in 200 l (330 kg net) metallic drums available on (1320 kg net) pallets.

http://www.solvaychlorinatedorganics.com/docroot/chlo_org/static_files/attachments/doc_2960_0012_w_en_ww.pdf

The recommended shelf life of drummed Perstabil® is two years from packaging date (printed on each drum).

Please consult our Safety Data Sheet:

http://www.solvaychlorinatedorganics.com/docroot/chlo_org/static_files/attachments/sds_2960_13684_w_en_ww.pdf

For other languages than English please contact us.

To our present knowledge, the information contained herein is accurate as of the date of this document. However, we do not make any warranty, express or implied, or accept any liability in connection with this information or its use. This information is for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. The user alone must finally determine suitability of any information or material for any contemplated use, the manner of use in compliance with relevant legislations and whether any patents are infringed. We reserve our right to make additions, deletions, or modifications to the information at any time without prior notification.

Solvay Chemicals
International



a Passion for Progress®