

## LOMON® R-996

**Titanium Dioxide Pigment** 

<mark>کـوثر شيـمی</mark> Kosar Shimi +9821 - 43462000 info@kosar.co www.kosar.co

## **PRODUCT DESCRIPTION**

LOMON<sup>®</sup> R-996 is Zirconia and Alumina treated rutile titanium dioxide pigment. It is proved to have excellent outdoor durability and super gloss in paint & coating, ink and plastic industries.

# APPLICATIONS

LOMDN<sup>®</sup> R-996 is recommended as a premium pigment for a variety of high quality powder coatings, water-born and solvent-born industrial and decorative coating, ink and plastics.

 $\sim$ 

TECHNIC	AL DATA	SHEET
	/	1/1

	>
ТУРЕ	R-996
Crystal Form	Rutile
Classification ISO591, DIN5591	R2
ASTM D476	
CAS No.	3463-67-7
TiO2 Content(%) min	(7/92
pH Value	(6.5~8.5)
Density(g/cm <sup>3</sup> )	
Oil Absorption (g/100g) max	22
Specific Resistance( $\Omega$ m) min	150
Average Particle Size(µ m)	0.23
Surface Treatment	Zirconia & Alumina, Organic

- The information in this publication is, to be best of our knowledge, true but since the conditions of use are beyond our control, the values provided are not to be considered as a warranty or to be implied in respect of such information.
- In every case caution must be exercised to avoid violation or infringement of statutory obligations and any rights belonging to a third party.
- We are, at all times, willing to study customer specific outlets involving our products in order to enable their most effective use.



## **COMPARABLE PRODUCT TEST REPORT**

#### **COATING SOLUTIONS:**

Alkyd Melamine Enamel Test:

Binder	32% coconut alkyd / butylated melamine=70/30 (solid)
Grinding	Red Devil 5400 Paint Conditioner
Enamel	Dry PVC 24%, Pig / Binder solid=1.2
Coating	For Gloss and Color evaluation, coated with 150 micron wet

For Gloss and Color evaluation, coated with 150 micron wet thick applicator on a glassplate and baked for 20 minutes at 130 degree Centigrade.

For Opacity evaluation, coated with 60 micron wet thick Barcoater on a black and white paper.

	<b>D</b> 001	~	~	~ ~
	R-996	Competitive A	Competitive B	Competitive C
Fineness of grinding S	(µ m)	(µ m)	(µ m)	(µ m)
For 3 min	7 37	20	17	15
9 min	(11)	27	13	12
15min	12	>/16	12	10
21min	10	15	10	8
40min	<5Q	1 12	<5	<5
60 Specular Gloss	89	5 81	89	90
Color	21			Č.
L	93.9	932	()) 94.0	94.0
a	-1.0	-0.9	0.9	-1.0
b	0.6	1.2	1 70.8 52	0.9
Whiteness	93.8	93.5	\$3,9	93.8
Opacity				$\int$
Y on black substrate	75.6	74.7	75.80((	75.7
Y on white substrate	84.7	83.9	84.8	(84.5)
Contrast Ratio	89.3	89.1	89.4	(89.6)

For information only

Not for regulatory purposes

## **SAFETY & HEALTH INSTRUCTION**

All Lomon TiO2 products including R996 are not hazardous article according to international standard. Material Safety Data Sheet will be provided.

### **PACKING & TRANSPORTION**

25KG, 500KG and 1000KG, seaworthy and suitable for container transportation

<mark>کـوثر شيـمی</mark> Kosar Shimi +9821 - 43462000 info@kosar.co www.kosar.co



<mark>کـوثر شيـمی</mark> Kosar Shimi +9821 - 43462000 info@kosar.co www.kosar.co

#### **Customer Support**

According to our world map guidance you can find the information of our region sales managers, please do not hesitate to contact us if you have any questions.