



ISO 9001:2000
Certificate No.: CH98/8032

ISO 14001:2004
Certificate No.: CH03/0112

OHSAS 18001:1999
Certificate No.: CH05/0675

Address:

No. 3, Taban St. ,
Valie – e – Asr St.,
Tehran - Iran

Tel:

(+98 21)82122700

Fax:

(+98 21)8867 4126-27

Web-site:

www.arpc-ir.net

E-mail:

Sales@arpc-ir.net

High Density Polyethylene

13

بازرگانی کوثر
Kosar Trading
+9821 - 43462000
info@kosar.co
www.kosar.co

Typical properties	Test method (DIN)	Unit	Value
MFI@190°C, 5 kg	DIN 53735	gr/10min	23
Density	DIN 53479	gr/ml	0.957
Notched Impact Strength	DIN 53453	mj/mm ²	≥2.7
Standard Yellow Index	DIN 6167	-	≤4

► Values shown are averages & are not to be considered as product specifications.

* Main application & Characteristics:

13 is a high density polyethylene grade, suitable for mass production injection moulding of articles in rapid shot sequence applications.

♦ Characteristics:

- Low distortion tendency.
- High hardness and rigidity.
- Good toughness.
- Good ESCR.

♦ Typical applications are:

- Transport and stacking crates particularly bottle crates.

* 13 is suitable for food contact.