

1) **Product Description :**  
" 7000" F is a high density polyethylene

کوشر شیمی  
Kosar Shimi  
+9821 - 43462000  
info@kosar.co  
www.kosar.co

2) **Application:**

- **Enhanced ultra thin film.**

3) **Typical Data**

PROPERTY	TEST	UNIT	TYPICAL VALUE*
Density (23 °C)	ISO 1183	g/cm <sup>3</sup>	0.952
Melt Flow Rate (190 °C/2.16kg)	ASTM D 1238	g/10min	0.04
Melt Flow Rate (190 °C/21.6 kg)	ASTM D 1238	g/10min	---
Stress at Yield Point	ASTM D 638	Kg/ cm <sup>2</sup>	250
Stress at Break	ASTM D 638	Kg/ cm <sup>2</sup>	390
Elongation at Break	ASTM D 638	%	Above 500
Izod Impact	ASTM D 256	kg.cm/cm	30
Stress Cracking Resistance	ASTM D 1693	hr	Above 600
Melting Point	ASTM D 2117	°C	131

\*Typical Values; not to be construed as specifications.

**Producer: Mehr Petrochemical Co.**  
**Licensor: Mitsui**  
**Packing: 25 kg Plastic Bag**

Petrochemical Commercial Co.( PCC)  
P.O. BOX: 19395/4619, TEHRAN-IRAN  
E-mail: [pcc@petrochem-ir.net](mailto:pcc@petrochem-ir.net)  
Web site: <http://petrochem-ir.net>

For more information please contact us at:  
Telefax: +98 21 88788987-88889672-88788007-88799537  
Telex: +98 21 216924-5