



ISO 9001:2008
Certificate No.: CH98/8032

ISO 14001:2004
Certificate No.: CH03/0112

OHSAS 18001:1999
Certificate No.: CH05/0675

Address:

No. 3, Taban St. ,
Valie – e – Asr St.,
Tehran - Iran

Tel:

(+98 21)82122700

Fax:

(+98 21)8867 4126-27

Web-site:

www.arpc-ir.net

E-mail:

Sales@arpc-ir.net

High Density Polyethylene

HD5211EA

کوثر شیمی
Kosar Shimi
+9821 - 43462000
info@kosar.co
www.kosar.co

Typical properties	Test method (ASTM)	Unit	Value
MFI@190°C, 2.16 kg	D1238	gr/10min	11
Density	D1505	gr/cm ³	0.951
Tensile Strength @ Yield	D638	Mpa	27
Tensile Modulus	D638	Mpa	-
Elongation @Break	D638	%	1000
Flexural Modulus	D790	Mpa	1000
Hardness	D2240	Shore D	66
Charpy Impact Resistance (Notched)	D256	Kj/m ²	6

► Values shown are averages & are not to be considered as product specifications.

❖ Main application & Characteristics:

HD5211EA is a high density polyethylene copolymer grade with a narrow molecular weight distribution, suitable for a wide range of injection moulding applications.

◆ Characteristics:

- Good flow.
- Good impact strength.

◆ Typical applications:

- House wares.
- Caps & closures.
- Toys.
- Pails.
- Cartridges.

* HD5211EA is not suitable for organoleptic applications.