



High Density Polyethylene

12

کوثر شیمی
Kosar Shimi
+9821 - 43462000
info@kosar.co
www.kosar.co

Typical properties	Test method (DIN)	Unit	Value
MFI@190°C, 5 kg	53735	gr/10min	28
Density	53479	gr/ml	0.950
Notched Impact Strength	53453	mj/mm ²	≥2.5
Standard Yellow Index	6167	-	≤4

► Values shown are averages & are not to be considered as product specifications.

* Main application & Characteristics:

12 is a high density polyethylene grade, suitable for mass production injection moulding of articles in rapid shot sequence applications.

◆ Characteristics:

- Easy flowing
- Virtually free from distortion.

◆ Typical applications are:

- Lightweight house-hold less hard and rigid than 11.

* 12 is suitable for food contact.



ISO 9001:2000
Certificate No.: CH98/8032

ISO 14001:2004
Certificate No.: CH03/0112

OHSAS 18001:1999
Certificate No.: CH05/0675

Address:

No. 3, Taban St. ,
Valie - e - Asr St.,
Tehran - Iran

Tel:

(+98 21)82122700

Fax:

(+98 21)8867 4126-27

Web-site:

www.arpc-ir.net

E-mail:

Sales@arpc-ir.net