



PVC S٦٥٣٢

١) Product Description:

PVC S٦٥٣٢ is a porous suspension thermoplastic polymer with high bulk density.

٢) Applications:

Principal application areas are:

- Rigid profiles
- Sheets
- Pipes

٣) Typical Data

Row material properties	Unit	Test method		Typical value*
		DIN	ISO	
K-Value	-	٥٣٧٢٦	١٦٢٨/٢	٦٥
Particle size distribution: sieve retention R retained on ٠.٠٦٣ mm screen retained on ٠.٢٥ mm screen	%	٤٦١٠	٤٦١٠	>٩٨ <٥
Volatile matter	%	-	١٢٦٩	<.٣
Apparent bulk density	g/ml	١.٠	٦.٠	٠.٥٨

*The values given above are **typical** test results which should be used as a guide only. They do not form the whole or part of a specification or guarantee.

٤) Processing

S٦٥٣٢ can be converted into moulding compounds with the usual additives by standard mixing techniques.

Mixtures containing S ٦٥٣٢ fuse rapidly and can be extruded at high output rates.

٥) Packaging, Delivery and Storage

The product is supplied in ٢٥-kg bags as well as in bulk form.

S ٦٥٣٢ should be stored dry and away from direct or indirect sources of heat. Please consult the safety data sheet for information about the safety precautions necessary for transport, storage, blending and processing.